(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 2 June 2005 (02.06.2005)

PCT

(10) International Publication Number WO 2005/050081 A1

(51) International Patent Classification⁷: 58/02, 13/02

F16L 21/03,

(21) International Application Number:

PCT/AU2004/001612

(22) International Filing Date:

19 November 2004 (19.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003906412

20 November 2003 (20.11.2003) AU

(71) Applicant (for all designated States except US): TYCO WATER PTY LIMITED [AU/AU]; 114 Albatross Road, Nowra, New South Wales 2541 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): MIESZELEWICZ, Gienek [AU/AU]; 16 Menzies Avenue, Brighton, Victoria 3186 (AU).

(74) Agent: GRIFFITH HACK; Level 3, 509 St Kilda Road, Melbourne, Victoria 3004 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF CORROSION PROTECTION AT A WELDED PIPE JOINT AND RESULTING JOINT



METHOD OF CORROSION PROTECTION AT WELDED RESTRAINED ELASTOMERIC PIPE JOINT

(57) Abstract: There is disclosed a pipe joint, and a method of forming a pipe joint, between two metallic pipes which have been internally and/or externally coated with a material to prevent corrosion. The joint includes a spigot and a socket, the socket having, or being formed with, an internal circumferential groove (6) that provides a seating for an elastomeric sealing ring (8), and forwardly of which groove an extension or lip (13) is provided which provides a welding location (14) remote from the sealing ring. The coating on the end of the socket if necessary is removed to facilitate welding, and the spigot has a heat sink member (9) to enable the lip of the socket to be welded to the metal of the spigot.